

Hino 300 916 AT LWB (FE3)

Convenience	Airconditioner	Manual	
	Electric Windows	Driver + Passenger	
	Storage Facilities	Standard	
Dimensions and Capacities	Cab to Axle (mm)	3630	
	Cab Width (excl. mirrors - mm)	1995	
	Frame Height Rear Axle (mm)	805	
	Frame Width Front (Outside - mm)	750	
	Front Overhang (mm)	1115	
	Front Track (mm)	1655	
	Fuel Tank Capacity (L)	150	
	Gross Vehicle Mass (GVM)	8500	
	Ground Clearance (mm)	195	
	Height (mm)	2230	
	Max. Homologated Body Width (mm)	2500	
	Maximum Body Length (mm)	6000	
	Overall Length (mm)	7250	
	Rear Overhang (mm)	1970	
Engine and Drivetrain	Rear Track (mm)	1590	
	Suggested Body Length (mm)	5500	
	Width Across Rear Wheels (mm)	2055	
	4 Stroke Compression Ignition	Standard	
	Aspiration	Turbo Intercooled	
	Compression Ratio : 1	18.1	
	Configuration	In-line	
	Engine Capacity (cc)	4009	
	Engine Make	Hino	
	Engine Oil Cooler	Standard	
	Euro Emission Status	Euro 3	
	Firing order	1-3-4-2	
	Maximum Engine Speed (rpm)	3100	
	Maximum Power (kW @ r/min)	100@2800 @	
	Maximum Torque (Nm @ r/min)	420@1400 @	
	Number of Cylinders	4	
	Front Axle	Number of Main Bearings	5
Number of Valves per Cylinders		4	
Type of Cylinders		Dry Liners	
Valve Configuration		Overhead	
Make		Hino	
Type		Reversed Elliot I-Beam	
Mass Data (kg)		A - Front	3100
		A - Rear	6200
		Body + Payload Allowance (approx.)	5885
		D/T	10300
	GA - Front	3100	
	GA - Rear	6200	
	GCM	10300	
	GVM	8500	
	Tare - Front	1670	
	Tare - Rear	945	
	Tare - Total (incl. Spare Wheel)	2615	
Model Info	V - Rating	8500	
	Application	Freight Carrier	
	Katashiki	XZU730R-WKTTLN3	
Rear Axle	Model Code	FE3	
	Housing Type	Full Floating	
	Make	Hino	
Safety	Ratio : 1	5.857	
	Microdot Vehicle Identification	Standard	
	Seat Belt Pre-tensioner	Driver + Passenger	
	Side Impact Beams	Standard	
Service Brakes	Transponder Key Immobiliser	Standard	
	ABS	Standard	
	Brake System - Front	Drum	
	Brake System - Rear	Drum	
	Dual Circuit	Standard	
Steering	Type	Vacuum Servo Hydraulic	
	Ratio :1	20.9	
	Steering Column	Tilt and Telescopic	
	Turning Radius Between Kerbs (mm)	7400	
Transmission	Turning Radius Between Walls (mm)	8100	
	Type	Recirculating Ball	
	Gear Ratio :1	3.742 0.634	
	Gearshift Operation	Automatic	

	Make	Hino
	Mechanism	Automatic
	Model	A860E
	No of Forward Gears	6
	Reverse Ratio :1	3.539
Wheels & Tyres	Front Tyre Rim	Steel
	Front Tyre Size	215-75R17.5
	No of Wheels Including Spare	7
	Rear Tyre Rim	Steel
	Rear Tyre Size	215-75R17.5
	Spare Tyre Rim	Steel